

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : C07C 17/20, 19/08	A1	(11) International Publication Number: WO 94/21579 (43) International Publication Date: 29 September 1994 (29.09.94)
(21) International Application Number: PCT/GB94/00497 (22) International Filing Date: 14 March 1994 (14.03.94) (30) Priority Data: 9306072.1 24 March 1993 (24.03.93) GB 9306089.5 24 March 1993 (24.03.93) GB (71) Applicant (for all designated States except US): IMPERIAL CHEMICAL INDUSTRIES PLC [GB/GB]; Imperial Chem- ical House, Millbank, London SW1P 3JF (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): BONNIFACE, David, William [GB/GB]; 15 Highbank Road, Kingsley, Near War- rington WA6 8AE (GB). SCOTT, John, David [GB/GB]; 3 Lindsay Walk, Cuddington, Near Northwich, Cheshire CW8 2YQ (GB). WATSON, Michael, John [GB/GB]; Flat 7, 6 Liverpool Road, Chester CH2 1AE (GB). (74) Agents: OLDROYD, Alan et al.; ICI Chemicals & Polymers Ltd., Intellectual Property Dept., P.O. Box 11, The Heath, Runcorn, Cheshire WA7 4QE (GB).		(81) Designated States: AU, BR, CA, CN, FI, JP, KR, NO, RU, UA, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>
(54) Title: PRODUCTION OF DIFLUOROMETHANE (57) Abstract A process for the production of difluoromethane comprising (a) contacting dichloromethane with hydrogen fluoride in the presence of a fluorination catalyst to produce a product stream comprising difluoromethane, monochloromonofluoromethane and unreacted starting materials and (b) separating difluoromethane from the product stream from step (a), wherein sufficient hydrogen fluoride is employed in the process such that during step (b) the molar ratio of hydrogen fluoride to monochloromonofluoromethane is at least about 100:1.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

PRODUCTION OF DIFLUOROMETHANE.

This invention relates to a process for the production of difluoromethane.

5 In recent years there has been increasing international concern that chlorofluorocarbons, which are used on a large scale around the world, may be damaging the earth's protective ozone layer and there is now in place international legislation to ensure
10 that their manufacture and use is completely phased out. Chlorofluorocarbons are used, for example, as refrigerants, as foam blowing agents, as cleaning solvents and as propellants for aerosol sprays in which the variety of applications is virtually
15 unlimited. Consequently, much effort is being devoted to finding suitable replacements for chlorofluorocarbons which will perform satisfactorily in the many applications in which chlorofluorocarbons are used but which will not have the aforementioned
20 damaging effect on the ozone layer. One approach in the search for suitable replacements has centred on fluorocarbons which do not contain chlorine but which contain hydrogen. The hydrofluorocarbon difluoromethane, also known as HFA 32, is of interest
25 as one such replacement, in particular in a blend thereof with other hydrofluoroalkanes, for example HFA 134a and HFA 125, as a replacement for R-22 and R-502 in refrigeration, air-conditioning and other applications.

30 Processes have been proposed for the production of difluoromethane. Thus, in US Patent No. 2,744,148, there is described a process for the production of difluoromethane comprising contacting dichloromethane with hydrogen fluoride in the presence of a
35 fluorination catalyst which comprises nickel, chromium, cobalt, copper or palladium carried on

aluminium fluoride. Many other catalysts have been proposed for use in the hydrofluorination of dichloromethane, for example, chromium fluoride on alumina in US 4,147,733; aluminium fluoride, chromium fluoride, mixtures thereof, aluminium fluoride on active carbon or ferric chloride on active carbon in EP 128510; chromium oxyfluoride in US 2,745,886 and chromia in GB 1,307,224.

However, a serious problem with the production of difluoromethane by the hydrofluorination of dichloromethane is that a substantial amount of a highly toxic by-product, monochloromonofluoromethane, HCFC 31, is produced as an intermediate. HCFC 31 has an estimated Occupational Exposure Limit of 10 parts per billion, and may be produced in substantial quantities, indeed as much as 20% or more of the product from the hydrofluorination of dichloromethane.

We have now found that, rather than following the obvious course in finding a solution to this problem, that is to search for conditions under which the production of HCFC 31 is reduced, the problem may be solved by suppressing the toxicity problems associated with the HCFC 31 which is produced.

According to the present invention there is provided a process for the production of difluoromethane comprising: (a) contacting dichloromethane with hydrogen fluoride in the presence of a fluorination catalyst to produce a product stream comprising difluoromethane, monochloromonofluoromethane and unreacted starting material and (b) separating difluoromethane from the product stream from step (a), wherein sufficient hydrogen fluoride is employed in the process such that during step (b) the molar ratio of hydrogen

fluoride to monochloromonofluoromethane is at least about 100:1.

5 Preferably during step (b) the molar ratio of hydrogen fluoride to monochloromonofluoromethane is at least about 150:1, more preferably at least about 200:1 and especially at least about 300:1.

10 The Occupational Exposure Limit (O.E.L.) for HCFC 31 is estimated at 10 parts per billion, whilst that for hydrogen fluoride is 3 parts per million. Whilst hydrogen fluoride is therefore toxic, it is estimated to be about 300 times less toxic than HCFC 31. Furthermore, the toxicity problems associated with hydrogen fluoride usually exist in reactions in which it is employed as the reagent, and in
15 particular where it is employed in hydrofluorination reactions. Thus, it has been the toxicity of hydrogen fluoride which has determined the safety requirements and thus costs associated with conventional hydrofluorination reactions.

20 The high toxicity of HCFC 31 however, produced in substantial quantities during the hydrofluorination of dichloromethane would exceed the toxicity of hydrogen fluoride in the process streams, thereby increasing the safety requirements, for
25 example the use of specialist high sensitivity equipment for detecting very low levels of HCFC 31, and thus costs of carrying out the hydrofluorination of dichloromethane.

30 We have found that where hydrogen fluoride is employed in sufficient quantity, then it may effectively reduce the problem of HCFC 31 by enhancing conversion of HCFC 31 to HFA 32 and at the same time diluting the HCFC 31 to concentrations below 30 ppb such that the highest concentration of
35 HCFC 31 at any point in the process is less than 30

ppb, preferably less than 10 ppb and especially less than 3 ppb. In this way, the predominant toxicity problem to be faced and monitored is that of hydrogen fluoride. Consequently, the equipment or plant in which the process is effected may be operated safely with respect to both hydrogen fluoride and HCFC 31 when it is provided with a system for monitoring and detecting levels of hydrogen fluoride below 5 parts per million.

In particular, the concentration of HCFC 31 may tend to increase during the separation of difluoromethane from the process stream, step (b) of the process, thereby causing a localised high concentration of HCFC 31. However, hydrogen fluoride remains with the HCFC 31 and thus if sufficient hydrogen fluoride is present in step (b), then this localised concentration of HCFC 31 may be maintained at an acceptable level.

Typically the separation step (b) is performed using distillation and difluoromethane and hydrogen chloride are recovered from the bottom of the distillation column whilst excess hydrogen fluoride, HCFC 31, and unreacted dichloromethane are obtained from the top of the column and recycled.

According to a preferred embodiment of the present invention there is provided a process for the production of difluoromethane comprising: (a) contacting dichloromethane with hydrogen fluoride in the presence of a fluorination catalyst to produce a product stream comprising difluoromethane, monochloromonofluoromethane and unreacted starting materials, (b) separating difluoromethane from the product stream from step (a) and (c) recovering difluoromethane and recycling HCFC 31 to step (a) wherein sufficient hydrogen fluoride is employed in

the process such that during step (b) the molar ratio of hydrogen fluoride to monochloromonofluoromethane is at least about 100:1.

5 Usually, where sufficient hydrogen fluoride is employed such that the ratio of hydrogen fluoride to monochloromonofluoromethane is at least 100:1 in step (b), the ratio of hydrogen fluoride to HCFC 31 will also be at least 100:1 for step (c) and step (a).

10 The amount of hydrogen fluoride which is required in order to achieve the required ratio of hydrogen fluoride to HCFC 31 will depend upon the conversion of dichloromethane and the selectivity to HCFC 31 and HFA 32, that is the amount of HCFC 31 produced in step (a) of the process, which depends
15 inter alia upon the conditions of temperature and pressure under which the process is operated and the choice of catalyst.

Furthermore, it is not essential that all the hydrogen fluoride is passed over the catalyst. Thus
20 additional hydrogen fluoride may, as required, be added to the process stream recovered from step (a) of the process in order to ensure that the required ratio of hydrogen fluoride to HCFC 31 is achieved in step (b). Preferably however, the process is provided
25 with a single hydrogen fluoride feed to step (a).

Overall, the molar ratio of hydrogen fluoride to dichloromethane which is fed to the process will be at least 5:1, and usually more than 10:1. There is generally no need to use more than about 100:1 and
30 the molar ratio of hydrogen fluoride to dichloromethane will usually be less than about 50:1. Where the yield of HCFC 31 in step (a) of the process is about 10%, the ratio of hydrogen fluoride to dichloromethane may be at least 10:1, whilst where
35 the yield of HCFC 31 in step (a) is

5%, the ratio of hydrogen fluoride to dichloromethane may be at least 5:1. Typically however, the yield of HCFC 31 may be as much as 15%.

5 The process is preferably operated on a continuous basis, with make-up hydrogen fluoride being fed to step (a) of the process and recycled HCFC 31 and unreacted dichloromethane being converted to HFA 32 in step (a) of the process.

10 The conditions of temperature and pressure and choice of catalyst employed in step (a) may be as described in the prior art, for example a temperature in the range from about 100°C to about 500°C, preferably from about 200°C to about 400°C. Atmospheric pressure may be employed, although
15 superatmospheric pressure, say up to about 30 bar, or subatmospheric pressures may be employed if desired. The catalyst may be a conventional fluorination catalyst, for example a catalyst based on chromia, chromium fluoride or chromium oxyfluoride, alumina,
20 aluminium fluoride or aluminium oxyfluoride, or a catalyst comprising a metal, for example nickel, cobalt, zinc, iron or copper supported upon chromia, magnesia and/or alumina.

25 We have further found that a fluorination catalyst comprising zinc or a compound of zinc and a metal oxide, fluoride or oxyfluoride may be employed to increase the selectivity of the process towards difluoromethane with a consequent decrease in the yield of HCFC 31 from the process. The increased
30 selectivity to difluoromethane provides a substantial benefit in reducing the levels of HCFC 31 produced, and thus allows less hydrogen fluoride to be employed whilst providing the molar ratio of hydrogen fluoride to HCFC 31 required by the present invention.

We prefer to employ a catalyst as described in one of EP 0502605 or PCT/GB93/00244, the disclosures of which are incorporated herein by reference.

5 Thus the metal of the metal oxide, fluoride or oxyfluoride, the amount of zinc, the catalyst preparation method, the catalyst prefluorination treatment, the form of the catalyst, catalyst regeneration treatment, and the presence of other
10 metals or compounds thereof in the catalyst may be as described for the catalysts in EP 0502605 or PCT/GB93/0024, the disclosures of which are incorporated herein by reference. We especially prefer a catalyst as described in EP 0502605.

15 Use of the preferred catalyst generally allows lower temperatures to be used than those employed in the prior art whilst the level of HCFC 31 produced may not be increased compared with the levels of HCFC 31 produced at higher temperatures using catalysts
20 previously proposed. The use of lower temperatures results in substantially longer catalyst lifetimes with a consequent reduction in the frequency with which the catalyst requires regeneration. The temperature is especially preferably in the range from about 170°C to about 340°C, and particularly in
25 the range from about 240°C to about 320°C.

The invention is illustrated but not limited by the following example.

30 Example.

10g of a zinc/chromium mixed oxide catalyst prepared by co-precipitation and comprising 8% by weight zinc was charged to a 1/2" diameter Inconel reactor tube and heated to 300°C in nitrogen.
35 Hydrogen fluoride was then passed over the catalyst

for 24 hours at 300°C and the reactor was then cooled to 250°C.

The reactor was pressurised to 10 bar in nitrogen, and dichloromethane and hydrogen fluoride were passed over the catalyst in the mole ratios indicated in Table 1. The vent gas from the reactor was scrubbed with water to remove hydrogen fluoride and hydrogen chloride, sampled and analysed by Gas Chromatography. The results are shown in Table 1.

TABLE 1.

HF:CH ₂ Cl ₂ (Mole ratio)	Off Gas Composition (Zv/v)			HF:CH ₂ FCI Off Gas Mole Ratio
	CH ₂ Cl ₂	CH ₂ ClF	CH ₂ F ₂	
27.1	1.0	7.1	92.0	391
21.3	2.3	10.0	87.7	213
19.6	2.8	11.1	86.1	175
12.5	7.4	9.4	83.1	123

Examples 2 and 3.

The procedure of example 1 was repeated except that the examples were performed at atmospheric pressure and the temperature and feed ratio of hydrogen fluoride to dichloromethane were as stated in Table 2 below. The results are also shown in Table 2 below.

TABLE 2.

5	HF:CH ₂ Cl ₂ (Mole ratio)	Temp (°C)	Off Gas Composition (%v/v)			HF:CH ₂ FCI Off-Gas Mole Ratio
			CH ₂ Cl ₂	CH ₂ ClF	CH ₂ F ₂	
10	(Example 2)					
	15.9	250	3.5	5.2	91.3	271
	(Example 3)					
15	16.1	200	34.7	11.3	54.0	134

Examples 4 to 7.

The procedure of examples 2 and 3 was repeated
except that the catalysts employed were as follows:

Example 4: Chromia having a surface area of 160 m²/g.

Example 5: 2% w/w zinc on alumina prepared by
impregnating gamma alumina having an initial surface
area of 180 m²/g with aqueous zinc chloride solution.

Examples 6 and 7: 2% w/w chromium on alumina prepared
by impregnating gamma alumina having an initial
surface area of 180 m²/g with aqueous chromium
chloride solution.

The conditions and results for example 4 to 7
are shown in Table 3 below.

TABLE 3.

5	HF:CH ₂ Cl ₂ (Mole ratio)	Temp (°C)	Off Gas Composition (%v/v)			HF:CH ₂ FCI Off-Gas Mole Ratio
			CH ₂ Cl ₂	CH ₂ ClF	CH ₂ F ₂	
10	(Example 4)					
	15.9	200	75.8	14.0	10.2	105
15	(Example 5)					
	16.9	200	64.1	15.6	20.3	107
20	(Examples 6 and 7)					
	12.8	200	89.5	8.7	1.8	149
	15.2	200	91.8	7.0	1.2	218

CLAIMS.

1. A process for the production of difluoromethane comprising (a) contacting dichloromethane with
5 hydrogen fluoride in the presence of a fluorination catalyst to produce a product stream comprising difluoromethane, monochloromonofluoromethane and unreacted starting materials and (b) separating
10 difluoromethane from the product stream from step (a), wherein sufficient hydrogen fluoride is employed in the process such that during step (b) the molar ratio of hydrogen fluoride to monochloromonofluoromethane is at least about 100:1.
- 15 2. A process as claimed in claim 1 in which the molar ratio of hydrogen fluoride to monochloromonofluoromethane is at least about 150:1.
- 20 3. A process as claimed in claim 1 in which additional hydrogen fluoride is added to the process stream recovered from step (a) in order to ensure that the required ratio of hydrogen fluoride to HCFC
31 is achieved during step (b).
- 25 4. A process for the production of difluoromethane comprising (a) contacting dichloromethane with hydrogen fluoride in the presence of a fluorination catalyst to produce a product stream comprising
30 difluoromethane, monochloromonofluoromethane and unreacted starting materials, (b) separating difluoromethane from the product stream from step (a) and (c) recovering difluoromethane and recycling HCFC
31 to step (a) wherein sufficient hydrogen fluoride is employed in the process such that during step (b)

the molar ratio of hydrogen fluoride to monochloromonofluoromethane is at least about 100:1.

5 5. A process as claimed in any one of claims 1 to 4
in which the separation step (b) comprises distilling
the product stream from step (a) whereby to separate
a bottom stream comprising difluoromethane and
hydrogen chloride from a top stream comprising
hydrogen fluoride, HCFC 31 and unreacted
10 dichloromethane.

15 6. A process as claimed in any one of claims 1 to 5
in which the fluorination catalyst comprises a metal
oxide, metal fluoride or oxyfluoride.

20 7. A process as claimed in claim 6 in which the metal
of the oxide, fluoride or oxyfluoride is at least one
of chromium, aluminium, zinc, nickel, cobalt, copper
and magnesium.

25 8. A process as claimed in claim 7 in which the
catalyst comprises zinc or a compound of zinc and a
metal oxide, fluoride or oxyfluoride in which the
metal of the oxide, fluoride or oxyfluoride is
chromium or aluminium.

30 9. A process as claimed in any one of claims 1 to 8
when carried in equipment provided with a system for
monitoring and detecting concentrations of hydrogen
fluoride below 5 parts per million.

35 10. A process as claimed in claim 9 in which step (a)
is effected at a temperature in the range from about
240°C to about 320°C.

INTERNATIONAL SEARCH REPORT

International application No.
PC1/GB 94/00497A. CLASSIFICATION OF SUBJECT MATTER
IPC 5 C07C17/20 C07C19/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 5 C07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US,A,2 745 886 (R.P. RUH ET AL.) 15 May 1956 cited in the application see column 6; claims ---	1
A	US,A,2 744 148 (R.P. RUH ET AL.) 1 May 1956 cited in the application see column 5; claims -----	1

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

16 May 1994

Date of mailing of the international search report

27. 05. 94

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

Bonnevalle, E

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/GB 94/00497

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-2745886		NONE	
US-A-2744148		NONE	